inTech Fiber Splicing Trailer Standard Features Model Comparison

Construction Features	5 X 8	6 X 10 SA	6 X 10 TA	7 X 12	8 X 12	7 X 12 Essentials
Fully Welded Aluminum Frame					•	
16" On Center Wall/Roof Studs	•			1.00	•	•
Fully Trussed Service Walk On Roof					•	•
Dexter Torsion Axles w/ Electric Brakes	(1) 3500#	(1) 3500#	(2) 3500#	(2) 3500#	(2) 3500#	(2) 3500#
Nitrogen Filled Tires For More Even Wear		•				
2-5/16" Ball Coupler w/ 7 Way Trailer Plug	•	•			•	•
2000lbs Manual Crank Jack						
Front Stabilizer Jacks	Optional	•	•			N/A
Rear Stabilizer Jacks		•				
Heavy-Duty Extruded Aluminum Front Corners		1 • •				•
One-Piece Aluminum Underbelly						•
3/4" Wood Sub-Floor w/ One-Piece Metal Underbe	lly 😐			•		•
Insulated Walls & Ceiling		•				•
One-Piece Aluminum Roof		•				
Heavy-Duty Rear Step Bumper						N/A

Exterior Features	5 X 8	6 X 10 5A	6 X 10 TA	7 X 12	8 X 12	7 X 12 Essentials	
Full Fiberglass Exterior				•	•	•	
LED Clearance/Tail Lights				•	•	•	
24" ATP Stoneguard		•			•		
12″ ATP Side Trim	•			•	•	N/A	
24" Rear Entrance Door		٠			•		
24" Side Entrance Door w/ Slide-Out Step	N/A	Optional	Optional	•	•	•	
Roof Mounted Whelen LED Strobe Light				•	•	•	
Roof Mounted Whelen LED Lighted Directional Arrow Board	•	•	•	•	•	N/A	
Surface Mounted LED Flood Lights	•	••				••	
Electrical Features							
5.5 kW Onan Commercial Generator w/ Remote	Start 🧕					N/A	
20 Gal In-Frame Generator Fuel Tank w/ Locking Fuel Door	•	•	•	•	•	N/A	
Automatic Transfer Switch				•	•	N/A	
50 AMP Load Center w/ 60 AMP Converter	•					•	
120V 20 AMP Electrical Outlets Interior/Exterior W/GFI	4/1	5/1	5/1	5/1	5/1	5/1	
12V Deep Cycle Battery w/ 12V Cut-Off Switch	•				•	•	
25' Motorbase Shore Cord					•	•	

Exterior Features	5 X 8	6 X 10 SA	6 X 10 TA	7 X 12	8 X 12	7 X 12 Essentials
Full Fiberglass Exterior	•	٠	٠			•
LED Clearance/Tail Lights	•	•	•	•	•	•
24" ATP Stoneguard	•					
12" ATP Side Trim	•	•		•	•	N/A
24" Rear Entrance Door		٠				•
24" Side Entrance Door w/ Slide-Out Step	N/A	Optional	Optional	•	•	•
Roof Mounted Whelen LED Strobe Light					•	•
Roof Mounted Whelen LED Lighted Directional Arrow Board	•	•	•	•	•	N/A
Surface Mounted LED Flood Lights						

Electrical Features

5.5 kW Onan Commercial Generator w/ Remote Start	•				1.0	N/A
20 Gal In-Frame Generator Fuel Tank w/ Locking Fuel Door	•	•	•	•	•	N/A
Automatic Transfer Switch					•	N/A
50 AMP Load Center w/ 60 AMP Converter	•	•		•	•	•
120V 20 AMP Electrical Outlets Interior/Exterior W/GFI	4/1	5/1	5/1	5/1	5/1	5/1
12V Deep Cycle Battery w/ 12V Cut-Off Switch	•	•			•	
25' Motorbase Shore Cord						

Popular Options	5 X 8	6 X 10 5A	6 X 10 TA	7 X 12	8 X 12	7 X 12 Essentials
Adjustable Height Interchangeable Coupler						•
Spare Tire On Steel Wheel		10.1			•	•
AM/FM/CD Stereo w/ Bluetooth (4) Interior Speakers	•					•
Exterior Aluminum Cone Holder	•				•	N/A
Island Table Kit w/ Wall Storage Loops					•	N/A
Locking Fuel Fill Door	•	•		•	•	N/A
Additional Overhead Cabinet - 48"						N/A
Locking ATP Generator Cover	•	•	•		•	N/A
Aluminum Cabinets IPO Laminate Cabinets		•				N/A
Upgrade to 7K Onan Commercial Gen. From 5.5K	•				•	N/A
Additional 5200 BTU Heater						N/A

CUSTOM OPTIONS AND CABINET LAYOUTS ARE AVAILABLE!